



SPEC. NUMBER

PRODUCT GROUP

REV.

ISSUE DATE

PAGE

TFT- LCD

A0

2021-10-14

1 OF 26

HBM215FH10B LCM 600nit Spec

ITEM	BUYER SIGNATURE	DATE
_____	_____	_____
_____	_____	_____
_____	_____	_____

ITEM	SUPPLIER SIGNATURE	DATE
Prepared	_____	_____
Reviewed	_____	_____
Approved	_____	_____

PRODUCT GROUP	REV	ISSUE DATE	
TFT- LCD PRODUCT	A0	2021-10-14	

SPEC. NUMBER	SPEC . TITLE	PAGE
	HBM215FH10B Product Specification	2 OF 26

REVISION HISTORY

REV.	ECN No.	DESCRIPTION OF CHANGES	DATE	PREPARED
A0		Initial Release	2021-10-14	

--	--	--	--	--

PRODUCT GROUP	REV	ISSUE DATE	
TFT- LCD PRODUCT	A0	2021-10-14	
SPEC. NUMBER	SPEC. TITLE		PAGE
	HBM215FH10B Product Specification		3 OF 26

Contents

No.	Items	Page
	REVISION HISTORY	2
	CONTENTS	3
1.0	General Description	4
2.0	Absolute Maximum ratings	6
3.0	Electrical specifications.	7
4.0	Optical specifications.	9
5.0	Interface Connection	14
6.0	Signal Timing Specification	16
7.0	Input Signals, Display Colors & Gray Scale of Colors	18
8.0	LVDS VESA Data Mapping	19
9.0	Power Sequence	20
10.0	Mechanical Characteristics	21
11.0	Reliability Test	22
12.0	Handling & Cautions.	22
13.0	Label	23
14.0	Packing information	24
15.0	Mechanical Outline Dimension	25


PRODUCT GROUP		REV	ISSUE DATE	
TFT- LCD PRODUCT		A0	2021-10-14	
SPEC. NUMBER	SPEC. TITLE			PAGE
	HBM215FH10B Product Specification			4 OF 26

1.0 GENERAL DESCRIPTION

1.1 Introduction

HBM215FH10B is a color active matrix TFT LCD FOB using amorphous silicon TFT's(Thin Film Transistors) as an active switching devices. This module has a 21.5 inch diagonally measured active area with FHD resolutions (1080 horizontal by 1920 vertical pixel array). Each pixel is divided into RED, GREEN, BLUE dots which are arranged in vertical Stripe and this module can display 16.7M colors. The TFT-LCD panel used for this module is a low reflection and higher color type. The LED Driver for back-light driving is built in this model.

All input signals are LVDS interface compatible.



1.2 Features

- LVDS Interface Support MIPI & Edp Interface in Qctober 2021
- High-speed response
- Real 8 bit color depth , display 16.7M colors
- DE (Data Enable) only
- Wide Temperature Range -20°C-70°C Operation Test
- Built In Self Test(BIST) Function
- Low driving voltage and low power consumption
- Normal Reverse type, Forward Type by choose

PRODUCT GROUP		REV	ISSUE DATE	
TFT- LCD PRODUCT		A0	2021-10-14	
SPEC. NUMBER	SPEC. TITLE			PAGE
	HBM215FH10B Product Specification			5 OF 26

1.3 Application

- White Goods

1.4 General Specification

The followings are general specifications at the QV215FHB-N11(FOB).

<Table 1. General Specifications>

Parameter	Specification	Unit	Remarks
Active Area	260.28(H)*478.656(V)	mm	
Number Of Pixels	1080(H)×1920(V)	pixels	
Pixel Pitch	80.33/80.33/80.34*249.3	um	
Pixel Arrangement	Pixels RGB stripe arrangement		
Display Mode	Normally Black		
Display Colors	16.7M	colors	
Luminance of LCM	600	nit	
Surface Treatment	AG25		
Contrast Ratio	1000:1(typ.)		
Viewing Angle(CR>10)	85/85/85/85(typ.)		
Response Time	30(typ.)	ms	
Color Gamut	72%NTSC		
Operation temperature	-20~70	°C	
Storage temperature	-30~80	°C	
Panel outline	267.28*489.956	mm	

PRODUCT GROUP		REV	ISSUE DATE	
TFT- LCD PRODUCT		A0	2021-10-14	
SPEC. NUMBER	SPEC. TITLE			PAGE
	HBM215FH10B Product Specification			6 OF 26

2.0 ABSOLUTE MAXIMUM RATINGS


The followings are maximum values which, if exceed, may cause faulty operation or damage to the unit.

< Table 2. Absolute Maximum Ratings >

Parameter		Symbol	Min.	Max.	Unit	Remarks
Power Supply	LCD Module	VDD	VSS-0.3	5.5	V	Ta = 25 °C Note 1&2
Operating Temperature		T _{OP}	-20	+70	°C	Note 3
Storage Temperature		T _{ST}	-30	+80	°C	
Operating Ambient Humidity		H _{op}	10	80	%RH	
Storage Humidity		H _{st}	10	80	%RH	

Note:

- These range above is maximum value not the actual operating temperature . Actual Operating temperature is no more than 40°C and temperature refers to the LCM surface temperature ; Length of operation: No more than 8 hours per day, and no more than 4 hours of continuous use one time.
- BOE is not responsible for product problems beyond the use conditions.
- Temperature and relative humidity range are shown in the figure below. Wet bulb temperature should be 39 °C max. and no condensation of water.



PRODUCT GROUP		REV	ISSUE DATE	
TFT- LCD PRODUCT		A0	2021-10-14	
SPEC. NUMBER	SPEC. TITLE			PAGE
	HBM215FH10B Product Specification			7 OF 26

3.0 ELECTRICAL SPECIFICATIONS

3.1 TFT LCD Module

< Table 3. LCD Module Electrical specifications > [Ta = 25 ± 2 °C]

Parameter		Min.	Typ.	Max.	Unit	Remarks
Power Supply Voltage	V_{DD}	4.5	5	5.5	V	Note 1
Permissible Input Ripple Voltage	V_{RF}	-	-	100	mV	At $V_{DD} = 3.3V$
Power Supply Current	I_{DD}	-	300	680	mA	Note 1
High Level Differential Input Threshold Voltage	V_{IH}	-	-	+100	mV	
Low Level Differential Input Threshold Voltage	V_{IL}	-100	-	-	mV	
Differential input voltage	$ V_{ID} $	0.2	0.4	0.6	V	
Differential input common mode voltage	V_{cm}	0.6	1.2	2.2	V	
Power Consumption	P_D	-	1.5	-	W	Note 1
	-	-	-	-	W	
	P_{total}	-	-	-	W	

Notes : 1. The supply voltage is measured and specified at the interface connector of FOB.
The current draw and power consumption specified is for 3.3V at 25°C.


a) Typ : Mosaic Pattern

Max: R G B Pattern

PRODUCT GROUP		REV	ISSUE DATE	
TFT- LCD PRODUCT		A0	2021-10-14	
SPEC. NUMBER	SPEC. TITLE			PAGE
	HBM215FH10B Product Specification			8 OF 26

3.2 Backlight Uint

Parameter		Min.	Typ.	Max.	Unit	Remarks
LED Light Bar Input Voltage Per Input Pin	VPIN	47.6	51	54.4	V	Duty 100%
LED Light Bar Input Current Per Input Pin	IPIN	-	60	-	mA	Note1,2
LED Power Consumption	P _{BL}	22.84	24.48	26.12	W	Note 3
LED Life-Time	-	30,000	-		Hrs	Note 4



LED: 17*4*2=136 PCS

LED bar consists of 136LED packages,4strings(parallel)*17packages(serial)*2

Note1: There are one light bar ,and the specified current is input LED chip 100% duty current

Note2: The sense current of each input pin is 60mA

Note3: $P_{BL}=2*4Input\ pins*VPIN \times IPIN$

Note4: The lifetime is determined as the time at which luminance of LED become 50% of the initial brightness or not normal lighting at IPIN=70mA on condition of continuous operating at $25 \pm 2 \text{ } ^\circ\text{C}$

PRODUCT GROUP		REV	ISSUE DATE	
TFT- LCD PRODUCT		A0	2021-10-14	
SPEC. NUMBER	SPEC. TITLE			PAGE
	HBM215FH10B Product Specification			9 OF 26

4.0 OPTICAL SPECIFICATION

4.1 Overview

The test of Optical specifications shall be measured in a dark room (ambient luminance ≤ 1 lux and temperature = $25 \pm 2^\circ\text{C}$) with the equipment of Luminance meter system (Goniometer system and TOPCON BM-5) and test unit shall be located at an approximate distance 50cm from the LCD surface at a viewing angle of θ and Φ equal to 0° . We refer to $\theta\emptyset=0$ ($=\theta_3$) as the 3 o'clock direction (the "right"), $\theta\emptyset=90$ ($=\theta_{12}$) as the 12 o'clock direction ("upward"), $\theta\emptyset=180$ ($=\theta_9$) as the 9 o'clock direction ("left") and $\theta\emptyset=270$ ($=\theta_6$) as the 6 o'clock direction ("bottom"). While scanning θ and/or \emptyset , the center of the measuring spot on the Display surface shall stay fixed. The backlight should be operating for 30 minutes prior to measurement. VDD shall be $3.3 \pm 0.3\text{V}$ at 25°C . Optimum viewing angle direction is 6 'clock.

4.2 Optical Specifications

<Table 4. Optical Specifications>

Parameter		Symbol	Condition	Min.	Typ.	Max.	Unit	Remark
Viewing Angle range	Horizontal	Θ_3	CR > 10	-	85	-	Deg.	Note 1
		Θ_9		-	85	-	Deg.	
	Vertical	Θ_{12}		-	85	-	Deg.	
		Θ_6		-	85	-	Deg.	
Luminance Contrast ratio		CR	$\Theta = 0^\circ$	900	1000	-	-	
Transmittance		Tr		3.5	3.9	-	%	FOB
Luminance of White	5 Points	Y_w	$\Theta = 0^\circ$	500	600	-	nit	
White Chromaticity		x_w	$\Theta = 0^\circ$	0.283	0.313	0.343	-	
		y_w		0.299	0.329	0.359	-	
Reproduction of color	Red	x_R	$\Theta = 0^\circ$	-0.03	0.649	+0.03	-	
		y_R			0.346		-	
	Green	x_G			0.329		-	
		y_G			0.623		-	
	Blue	x_B			0.151		-	
		y_B			0.064		-	
Gamut		-	-	68	72	-	%	
Response Time (Rising + Falling)		T_{RT}	$T_a = 25^\circ\text{C}$ $\Theta = 0^\circ$	-	30	35	Ms	Note 6
Cross Talk		CT	$\Theta = 0^\circ$	-	-	2	%	

PRODUCT GROUP		REV	ISSUE DATE	
TFT- LCD PRODUCT		A0	2021-10-14	
SPEC. NUMBER	SPEC. TITLE			PAGE
	HBM215FH10B Product Specification			10 OF 26

Notes :

1. Viewing angle is the angle at which the contrast ratio is greater than 10. The viewing angles are determined for the horizontal or 3, 9 o'clock direction and the vertical or 6, 12 o'clock direction with respect to the optical axis which is normal to the LCD surface (see FIGURE 1).

2. Contrast measurements shall be made at viewing angle of $\Theta = 0$ and at the center of the LCD surface. Luminance shall be measured with all pixels in the view field set first to white, then to the dark (black) state .
(see FIGURE 1) Luminance Contrast Ratio (CR) is defined mathematically.

3. Center Luminance of white is defined as luminance values of 5 point average across the LCD surface. Luminance shall be measured with all pixels in the view field set first to white. This measurement shall be taken at the locations shown in FIGURE 2 for a total of the measurements per display.

4. The White luminance uniformity on LCD surface is then expressed as : $\Delta Y = \text{Minimum Luminance of 5(or 13) points} / \text{Maximum Luminance of 5(or 13) points}$.
(see FIGURE 2 and FIGURE 3).

5. The color chromaticity coordinates specified in Table 5 shall be calculated from the spectral data measured with all pixels first in red, green, blue and white. Measurements shall be made at the center of the panel.

6. The electro-optical response time measurements shall be made as FIGURE 4 by switching the "data" input signal ON and OFF. The times needed for the luminance to change from 10% to 90% is T_r , and 90% to 10% is T_d .

7. Cross-Talk of one area of the LCD surface by another shall be measured by comparing the luminance (YA) of a 25mm diameter area, with all display pixels set to a gray level, to the luminance (YB) of that same area when any adjacent area is driven dark.
(See FIGURE 5).

PRODUCT GROUP		REV	ISSUE DATE	
TFT- LCD PRODUCT		A0	2021-10-14	
SPEC. NUMBER	SPEC. TITLE		PAGE	
	HBM215FH10B Product Specification		11 OF 26	

4.3 Optical measurements

Figure 1. Measurement Set Up






Figure 2. White Luminance and Uniformity Measurement Locations (5 points)



Center Luminance of white is defined as luminance values of center 5 points across the LCD surface. Luminance shall be measured with all pixels in the view field set first to white. This measurement shall be taken at the locations shown in FIGURE 2 for a total of the measurements per display.


PRODUCT GROUP		REV	ISSUE DATE
TFT- LCD PRODUCT		A0	2021-10-14
SPEC. NUMBER	SPEC. TITLE		PAGE
	HBM215FH10B Product Specification		12 OF 26

Figure 3. Uniformity Measurement Locations (13 points)



The White luminance uniformity on LCD surface is then expressed as : $\Delta Y5 = \text{Minimum Luminance of five points} / \text{Maximum Luminance of five points}$ (see FIGURE 2) , $\Delta Y13 = \text{Minimum Luminance of 13 points} / \text{Maximum Luminance of 13 points}$ (see FIGURE 3).


Figure 4. Response Time Testing



The electro-optical response time measurements shall be made as shown in FIGURE 4 by switching the “data” input signal ON and OFF. The times needed for the luminance to change from 10% to 90% is T_d and 90% to 10% is T_r .

PRODUCT GROUP		REV	ISSUE DATE	
TFT- LCD PRODUCT		A0	2021-10-14	
SPEC. NUMBER	SPEC. TITLE		PAGE	
	HBM215FH10B Product Specification		13 OF 26	

Figure 5. Cross Modulation Test Description



$$\text{Cross-Talk (\%)} = \left| \frac{Y_B - Y_A}{Y_A} \right| \times 100$$

Where:

- Y_A = Initial luminance of measured area (cd/m²)
- Y_B = Subsequent luminance of measured area (cd/m²)

The location measured will be exactly the same in both patterns


Cross-Talk of one area of the LCD surface by another shall be measured by comparing the luminance (Y_A) of a 25mm diameter area, with all display pixels set to a gray level, to the luminance (Y_B) of that same area when any adjacent area is driven dark (Refer to FIGURE 5).

PRODUCT GROUP		REV	ISSUE DATE	
TFT- LCD PRODUCT		A0	2021-10-14	
SPEC. NUMBER	SPEC. TITLE		PAGE	
	HBM215FH10B Product Specification		14 OF 26	

5.0 INTERFACE CONNECTION.

5.1 LED Light Bar

LED Connector:



PRODUCT GROUP		REV	ISSUE DATE	
TFT- LCD PRODUCT		A0	2021-10-14	
SPEC. NUMBER	SPEC. TITLE			PAGE
	HBM215FH10B Product Specification			15 OF 26

5.0 INTERFACE CONNECTION.

5.2 LVDS Interface Connection

The electronics interface connector is UJU IS100-L30R-C23or Equivalent.

< Table 5. FOB Pinmap >

Terminal	Symbol	Functions
Pin No.	Symbol	Description
1	RX00-	Negative Transmission data of Pixel 0 (ODD)
2	RX00+	Positive Transmission data of Pixel 0 (ODD)
3	RX01-	Negative Transmission data of Pixel 1 (ODD)
4	RX01+	Positive Transmission data of Pixel 1 (ODD)
5	RX02-	Negative Transmission data of Pixel 2 (ODD)
6	RX02+	Positive Transmission data of Pixel 2 (ODD)
7	STBYB(NC)	*Reserved for LCD manufacturer's use (No Connection)
8	RXOC-	Negative Transmission Clock (ODD)
9	RXOC+	Positive Transmission Clock (ODD)
10	RX03-	Negative Transmission data of Pixel 3 (ODD)
11	RX03+	Positive Transmission data of Pixel 3 (ODD)
12	RXE0-	Negative Transmission data of Pixel 0 (EVEN)
13	RXE0+	Positive Transmission data of Pixel 0 (EVEN)
14	GND	Power Ground
15	RXE1-	Negative Transmission data of Pixel 1 (EVEN)
16	RXE1+	Positive Transmission data of Pixel 1 (EVEN)
17	GND	Power Ground
18	RXE2-	Negative Transmission data of Pixel 2 (EVEN)
19	RXE2+	Positive Transmission data of Pixel 2 (EVEN)
20	RXEC-	Negative Transmission Clock (EVEN)
21	RXEC+	Positive Transmission Clock (EVEN)
22	RXE3-	Negative Transmission data of Pixel 3 (EVEN)
23	RXE3+	Positive Transmission data of Pixel 3 (EVEN)
24	GND	Power Ground
25	CTL	*Reserved for LCD manufacturer's use (CTL_DVR)
26	CE	*Reserved for LCD manufacturer's use (CE_DVR)
27	NC	No Connection
28	VDD	Power Supply: +5V(4.5V~5.5V)
29	VDD	
30	VDD	

PRODUCT GROUP		REV	ISSUE DATE	
TFT- LCD PRODUCT		A0	2021-10-14	
SPEC. NUMBER	SPEC. TITLE			PAGE
	HBM215FH10B Product Specification			16 OF 26

6.0 SIGNAL TIMING SPECIFICATION

6.1 The QV215FHB-N11 is operated by the DE only.

< Table 6. FOB Timing Spec >



Item		Symbols	Min	Typ	Max	Unit
Frequency		1/Tc	--	61.86	--	MHz
Horizontal	Frame Rate	F	58	60	62	Hz
	Total	T _H	580	580	594	T _H
	Display	T _{HD}	540			T _H
	Blank	T _{HB}	40	40	54	T _H
Vertical	Total	T _V	1950	1950	2112	T _{CLK}
	Display	T _{VD}	1920			T _{CLK}
	Blank	T _{VB}	30	30	192	T _{CLK}

PRODUCT GROUP		REV	ISSUE DATE	
TFT- LCD PRODUCT		A0	2021-10-14	
SPEC. NUMBER	SPEC. TITLE		PAGE	
	HBM215FH10B Product Specification		17 OF 26	

6.2 LVDS Rx Interface Timing Parameter

<Table 7. LVDS Rx Interface Timing Specification>


Item	Signal	Symbol	Rating			Unit
			Min.	Typ.	Max.	
Clock Frequency	CLK	R _X FCLK	20	-	100	MHz
Clock Period		R _X TCLK	10	-	50	ns
1 data bit time		UI	-	1/7	-	R _X TCLK
Clock high time	CLK	T _{LVCH}		4		UI
Clock low time		T _{LVCL}		3		UI
Position 1	DATA	T _{POS1}	-0.25	0	0.25	UI
Position 2		T _{POS2}	0.75	-	1.25	
Position 3		T _{POS3}	0.75	1	1.25	
Position 4		T _{POS4}	1.75	-	2.25	
Position 5		T _{POS5}	1.75	2	2.25	
Position 6		T _{POS6}	2.75	-	3.25	
Position 7		T _{POS7}	2.75	3	3.25	
Position 8		T _{POS8}	3.75	-	4.25	
Position 9		T _{POS9}	3.75	4	4.25	
Position 10		T _{POS10}	4.75	-	5.25	
Position 11		T _{POS11}	4.75	5	5.25	
Position 12		T _{POS12}	5.75	-	6.25	
Position 13		T _{POS13}	5.75	6	6.25	
Position 14		T _{POS14}	6.75	-	7.25	
PLL wake-up time		T _{enPLL}	-		150	us



PRODUCT GROUP		REV	ISSUE DATE
TFT- LCD PRODUCT		A0	2021-10-14
SPEC. NUMBER	SPEC. TITLE		PAGE
	HBM215FH10B Product Specification		18 OF 26

7.0 SIGNAL TIMING WAVEFORMS OF INTERFACE SIGNAL


Figure 6. signal Timing



PRODUCT GROUP		REV	ISSUE DATE	
TFT- LCD PRODUCT		A0	2021-10-14	
SPEC. NUMBER	SPEC. TITLE			PAGE
	HBM215FH10B Product Specification			19 OF 26

8.0 LVDS VESA Data Mapping

Figure 7. Data Mapping




Note 1 : for 6 bit mode, MSB are R/G/B[5] and R/G/B[0] are LSB
 Note 2 : for 8 bit mode, MSB are R/G/B[7] and R/G/B[0] are LSB

PRODUCT GROUP		REV	ISSUE DATE	
TFT- LCD PRODUCT		A0	2021-10-14	
SPEC. NUMBER	SPEC. TITLE			PAGE
	HBM215FH10B Product Specification			20 OF 26

9.0 POWER SEQUENCE

To prevent a latch-up or DC operation of the LCD module, the power on/off sequence shall be as shown in below



Parameter	Values			Units
	Min	Typ	Max	
T1	0.5	-	10	ms
T2	10	-	60	ms
T4	200	-	-	ms
T5	200	-	-	ms
T7	0	-	50	ms
T8	0.5	-	20	ms
T9	1000	-	-	ms
-	-	-	-	ms
-	-	-	-	ms

PRODUCT GROUP		REV	ISSUE DATE	
TFT- LCD PRODUCT		A0	2021-10-14	
SPEC. NUMBER	SPEC. TITLE		PAGE	
	HBM215FH10B Product Specification		21 OF 26	

10.0 MECHANICAL CHARACTERISTICS

10.1 Dimensional Requirements

FIGURE 6 shows mechanical outlines for the model QV215FHB-N11.
Other parameters are shown in Table 8.

<Table 8. Dimensional Parameters>

Parameter	Specification	Unit
Active Area	260.28(H)*478.656(V)	mm
Number of pixels	1080 (H) x 1920 (V)	
Pixel pitch	0.1335(H)×0.1335(V)	mm
Pixel arrangement	RGB Vertical stripe	
Display colors	16.7M	
Display mode	Normally Black	
Dimensional outline	292.2 (H)*495.6(V) *8.0(D)typ	mm
Weight	-	gram

10.2 Mounting

See FIGURE 6.

10.3 AG and Polarizer Hardness.

The surface of the LCD has a Anti Glare coating to minimize reflection and a coating to reduce scratching.

10.4 Light Leakage

Light Leakage shall be checked by naked eye Applying Limit sample and/or 10% ND filter with conditions as follow:

1. With a viewing distance of 500mm from the screen.
2. With overhead light less than 350lux
3. Viewing angle Within 45 degrees at Left/Right/Upper/Lower.
4. Check pattern with Black, White and 32-gray (Half-gray) screens.

PRODUCT GROUP		REV	ISSUE DATE	
TFT- LCD PRODUCT		A0	2021-10-14	
SPEC. NUMBER	SPEC. TITLE			PAGE
	HBM215FH10B Product Specification			22 OF 26

11.0 RELIABILITY TEST

The Reliability test items and its conditions are shown in below.

<Table 9. Reliability test>

No	Test Items	Conditions
1	High temperature storage test	Ta = 80 °C, 72 hrs
2	Low temperature storage test	Ta = -30 °C, 72 hrs
3	High temperature & high humidity (operation test)	Ta = 50 °C, 80%RH, 72 hrs
4	High temperature operation test	Ta = 70 °C, 72 hrs
5	Low temperature operation test	Ta = -20 °C, 72 hrs
6	Thermal shock	Ta = -20 °C ↔ 60 °C (1 hr), 100 cycle
7	Drop (non-operating)	60cm/1 corner/3 edges/6 faces
8	Shock test (non-operating)	220G, Half Sine Wave 2msec ±X, ±Y, ±Z Once for each direction
9	Electro-static discharge test (non-operating)	Air : 150 pF, 330Ω, 15 KV Contact : 150 pF, 330Ω, 8 KV

12.0 HANDLING & CAUTIONS

(1) Cautions when taking out the module

- Pick the pouch only, when taking out module from a shipping package.

(2) Cautions for handling the module

- As the electrostatic discharges may break the LCD module, handle the LCD module with care. Peel a protection sheet off from the LCD panel surface as slowly as possible.
- As the LCD panel and back - light element are made from fragile glass material, impulse and pressure to the LCD module should be avoided.
- As the surface of the polarizer is very soft and easily scratched, use a soft dry cloth without chemicals for cleaning.
- Do not pull the interface connector in or out while the LCD module is operating.
- Put the module display side down on a flat horizontal plane.
- Handle connectors and cables with care.

(3) Cautions for the operation

- When the module is operating, do not lose CLK, ENAB signals. If any one of these signals is lost, the LCD panel would be damaged.
- Obey the supply voltage sequence. If wrong sequence is applied, the module would be damaged.

PRODUCT GROUP		REV	ISSUE DATE	
TFT- LCD PRODUCT		A0	2021-10-14	
SPEC. NUMBER	SPEC. TITLE		PAGE	
	HBM215FH10B Product Specification		23 OF 26	

(4) Cautions for the atmosphere

- Dew drop atmosphere should be avoided.
- Do not store and/or operate the LCD module in a high temperature and/or humidity atmosphere. Storage in an electro-conductive polymer packing pouch and under relatively low temperature atmosphere is recommended.

(5) Cautions for the module characteristics

- Do not apply fixed pattern data signal to the LCD module at product aging.
- Applying fixed pattern for a long time may cause image sticking.

(6) Other cautions

- Do not disassemble and/or re-assemble LCD module.
- Do not re-adjust variable resistor or switch etc.
- When returning the module for repair or etc., Please pack the module not to be broken. We recommend to use the original shipping packages.

13.0 LABEL

TBD

PRODUCT GROUP	REV	ISSUE DATE	
TFT- LCD PRODUCT	A0	2021-10-14	
SPEC. NUMBER	SPEC. TITLE		PAGE
	HBM215FH10B Product Specification		24 OF 26


14.0 PACKING INFORMATION

TBD

PRODUCT GROUP		REV	ISSUE DATE	
TFT- LCD PRODUCT		A0	2021-10-14	
SPEC. NUMBER	SPEC. TITLE		PAGE	
	HBM215FH10B Product Specification		25 OF 26	

15.0 MECHANICAL OUTLINE DIMENSION

Figure 6. Outline Dimensions (Front view)



PRODUCT GROUP		REV	ISSUE DATE	
TFT- LCD PRODUCT		A0	2021-10-14	
SPEC. NUMBER	SPEC. TITLE			PAGE
	HBM215FH10B Product Specification			26 OF 26

15.0 MECHANICAL OUTLINE DIMENSION

Figure 7. Outline Dimensions (Rear view)

